8 7 6	5 4	3
PIN 3 DETAIL A SCALE 2 : 1	PIN 4	REV DATE C 12/30/16
) BLACK
TABLE 1 ITEM 4 WIRE COLOR BA5590-MP PIN BLACK 1 RED 5 2 JUMPED TO 4 BILL OF MATERIALS	RED	
ITEM NO.PART NUMBERQTYNAMECOMMENTS130"18 AWG2C CABLE. 5.0MM OD.2BA55902BA-5590 MALECONNECTOR3UL1332 TEFLON3"20 AWG2C CABLE. 4.6MM OD4SB12452DIODE45V, 12 AMP	JUMPER	
5 YS14-0675 1 Y SPLITTER NOTES: 1. CONNECT WIRING PER FIGURE 1 AND TABLE 1 2. SOLDERING IAW IPC-J-STD-001 CLASS II AS APPLICABLE. 3. CABLE ASSEMBLIES TO BE 100% TESTEDFOR CONTINUITY, S (250V @100MOHM MINIMUM) 4. IDENTIFICATION: BAG AND INDENTIFY ON PACKAGING TH PART DELIVERED. UOS PART MARKING ON THE WIRE IS PROPIN: SN-333 REV X (REV MARKING PER PO) CAGE CODE: 1HJX9 DATE OF MFGR: MM/YY 5. REFERENCE SUPPLYNET FILE NUMBER SN0244. 6. MANUFACTURE AND INSPECT IAW IPC/WHMA A-620 CLASS	HORTS AND INSULATION RESISTANCE HE FOLLOWING INFORMATION FOR EACH DHIBITED:	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN: INCHES TOLERANCES: .XX: ± 0.03 .XX: ± 0.005 ANGULAR: X*: 1° .XX: ± 0.05° BREAK EDGES: .005020 SUFACE FINISH: GEOMETRIC TOLERANCING PER: ASME Y14.5 -2009 MATERIAL: SEE DRAWING NOTES FINISH: SEE DRAWING NOTES DO NOT SCALE DRAWING A 3
	PIN 3 DETAIL A SCALE 2 : 1 PIN 2 PIN 2	PIN 3 PIN 4 DETAIL A SCALE 2: 1 DETAIL A SCALE 2: 1 PIN 1 Im 2 Im 1 Im 1 Im 1 Im 1 Im 2 Im 2

