


| | | 2 | | | | 1 | | |
|---|--|---|---------------|--------------------------|-----------|-----------------|----------|---|
| | F | REVISIO | NS | | | | |] |
| | ION | | | DATE | | ENC | | - |
| AL RE | V. | | | 10/27/22 | | MOE | 3 | |
| | | | | X | 201 | | | D |
| | | | | | | | | С |
| CT N FC | COL | OR IS BICLARITY. | LACK | | | | | B |
| | | | | JMBER: S | NI0270 |) | | _ |
| | NAME | DATE | | | 706 EXECL |) ITIVE BLVD | | |
| | мов | 10/27/22 | Supply | net | SUITE B | OTTAGE, NY | 10989 | |
| S: | RB | 10/27/22 | TITLE: AN/ | /PRC-1 WED | | | RY | A |
| Mation Is the I, INC. R AS A ERMISS TED. | N CONTAI SOLE PRO ANY REPR WHOLE W ION OF SL | IFIDENTIAL INED IN THIS PERTY OF CODUCTION VITHOUT THE IPPLYNET INC. | B S | 'G. NO. N-832- | | | REV A | - |
| ECC | DDE: 1 | HJX9 | SCALE: N | IA WEIGH | T: | SHEET | 1 OF 2 | |
| 1 | | 2 | | 1 | | 1 | | |



| BILL OF MATERIALS | | | | | | |
|-------------------|---|--|--|--|--|--|
| QTY | NAME/DESCRIPTION | | | | | |
| 1 | TOP COVER | | | | | |
| 1 | CONTACT ASSEMBLY | | | | | |
| 1 | CONTACT O-RING | | | | | |
| 1 | INSULATOR PLATE | | | | | |
| 4 | #4x1/4 FLAT HEAD SCREW | | | | | |
| 3 | 4-40 HEX NUT | | | | | |
| 1 | SEALING GASKET | | | | | |
| 2 | STEEL GROUND TABS | | | | | |
| 1 | O-RING FACE SEAL | | | | | |
| 2 | 4-40 FLAT HEAD PHILIPS SCREW, SS, 3/8" | | | | | |
| 1 | SPACER, M8x1.25 THREADED CABLE EXIT, SINGLE | | | | | |
| - | ТАВ | | | | | |
| 1 | ROCKER ARM, LOCKING BUTTON | | | | | |
| 1 | SPRING, LOCKING BUTTON | | | | | |
| 1 | LOCKING BUTTON | | | | | |
| 1 | BOTTOM COVER, 3 HOLES | | | | | |
| 1 | RED TEFLON COATED BUNA O-RING | | | | | |
| 1 | POGO PIN ASSEMBLY | | | | | |
| 1 | STAMPED GROUND BAR | | | | | |
| 3 | PHILLIPS FLAT HEAD SCREW, BLACK OXIDE, | | | | | |
| 5 | 1- 1/2" LONG | | | | | |
| 2 | 4-40 5/8" LONG SS, FLAT HEAD PHILLIPS SCREW | | | | | |
| 1 | AWG 20, 4C + DRAIN, FOIL SHIELD, WITH M8x1.25 | | | | | |
| - | THREADED STRAIN RELIEF | | | | | |