	8		7		6	5		4	3	
							1777		REV	DATE
	SN0832 Wire Run List								A	10/20/
	CONN-MBITR	Wire Color	SN-799	1						
	Pin 1	RED	Pin 1		Pi	n Detail			Pin	1
D	Pin 2 Pin 3	White RED	Pin 2 Pin 3			Pin 1—				-
D	Steel Tabs	Green + Drain	Steel Tabs				Pín1			
		Shrink Boot Drain								
		Wire Inside Box								~
	Wire Lenth 6 feet					Pin 3—	Pin 3/			Ň
						1115			Pin 3	
				- 6FT ±2"►						
С							_			
							<u>ه</u> کر		63	
->	7									
	H -									
										<u> </u>
		7 7								
В								11 🚯		
								<u>ا</u> @ /	®	
	H -				Pin [Detail		~~~		
	SN	N-799 SIDE			1 11 1 2			0	NN-MBITR SIDE	
									UNLESS OTHERWISE SPECIFIED	: SN031
А					<u> </u>				DIMENSIONS ARE IN: INCHES TOLERANCES: .XX: ± 0.03	DRAWN
					Щ				TOLERANCES: .XX: ± 0.03 .XXX: ± 0.005 ANGULAR: .X°: 1°	CHECKED
А					<u> </u>				.XX°: 0.5° BREAK EDGES: .005020 FILLETS: .005020	COMMENTS:
									SUFACE FINISH:	PROPRIET
					<u>_</u>				GEOMETRIC TOLERANCING PER: ASME Y14.5 -2009	THE INFORMA DRAWING IS
									MATERIAL: SEE DRAWING NOTES	SUPPLYNET, IN IN PART OR A WRITTEN PER
									FINISH: SEE DRAWING NOTES	
	8		7		6	5	Ą	4	3	CAGE
	0		•		-	•			0	



