

REVISIONS								
REV.	DESCRIPTION	DATE	ENG					
В	UPDATED DWG FORMAT, UPDATED TO M8 THREADED SR	6/21/2023	МОВ					
С	TABLE 2: WIRE LENGTH TABLE ADDED	3/26/2024	CWA					
D	ISO VIEW ADDED	3/26/2024	CWA					

BILL OF MATERIALS ITEM NO. PART NO. QTY NAME/DESCRIPTION BA-5590 CONNECTOR WITH VELCRO STRAP, M8 X CONN-BA5590-MTV 1.25 THREADED BACKSHELL. 202C-U07A -XX 2C, AWG 20, PU JACKET, .181 IN. DIA. SR:0024 M8 X 1.25 THREADED SR 3 1 SBM1060LSS AY 00001 2 60V, 10A, DIODE OR EQUIV.

				REF.	number: s	N0617		
UNLESS OTHERWISE SPECIFIED:		NAME	DATE		SupplyNet	DESIGN	-	
DIMENSIONS ARE IN: INCHES	DRAWN	MOB	4/3/2023		anhhiduci		ENGINEERING MANUFACTURING	
TOLERANCES: .XX: ± 0.03 .XXX: ± 0.005	CHECKED	RB	4/3/2023	TITLE:				
ANGULAR: .X*: 1* .XX*: 0.5* BREAK EDGES: .005020 FILLETS: .005020 SUFACE FINISH:	COMMENTS:			BA-5590 24VDC CABLE WITH VELCRO STRAP				
GEOMETRIC TOLERANCING PER: ASME Y14.5 -2009	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SUPPLYNET, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SUPPLYNET INC. IS PROHIBITED.		SIZE DWG. NO. REV					
MATERIAL: SEE DRAWING NOTES			B 191004F-VS-XX					
FINISH: SEE DRAWING NOTES								
DO NOT SCALE DRAWING	CAGEC	ODE: 1	I II I Y O	SCAI	IE NA WEIGH	ıτ·	SHEE	T 1 OF 1

NOTES:

WIRING SHALL BE DONE IN ACCORDANCE WITH TABLE 1 WIRE RUN LIST.

MARKING REQUIREMENTS:

A. EACH COMPLETED ASSEMBLY SHALL BE PLACED IN A ZIP-POLY BAG.

B. ZIP-POLY BAG SHALL BE MARKED WITH SUPPLYNET LOGO & PRODUCT QR CODE PER SN-STD-LBL. SOLDERING: IAW IPC-J-STD-001 CLASS 2 AS APPLICABLE

ASSEMBLY TO BE 100% TESTED FOR SHORTS, CONTINUITY, AND JACKET RESISTANCE (250V @ 100MOHM MIN.)

MANUFACTURE AND INSPECT IAW IPC/WHMA A-620 CLASS 2.

3