

NOTES:

- CABLE: 26 AWG, 12 CONDUCTOR, OD: 0.230 NOMINAL. POLYURETHANE INSULATION. OUTER SHIELD 38 AWG, TIN PLATED COPPER BRAID, 90% COVERAGE. C&M PN 51245.
- PRE-MOLD USING TOOLING PN 1071557
- **OVERMOLD USING TOOLING PN 1071558**
- OVERMOLD MATERIAL: 90A POLYETHER-TYPE THERMOPLASTIC POLYURETHANE (TPU).
- JACKET: BLACK MATTE FINISH.

- E33,E34 IS CHASSIS GROUND SOLDERING IAW IPC-J-STD-001 CLASS II AS APPLICABLE. CABLE ASSEMBLIES TO BE 100% TESTEDFOR CONTINUITY, SHORTS AND INSULATION RESISTANCE (250V @100MOHM MINIMUM)
- IDENTIFICATION: BAG AND INDENTIFY ON PACKAGING THE FOLLOWING INFORMATION FOR EACH PART DELIVERED. UOS PART MARKING ON THE WIRE IS PROHIBITED:

PN: TE-32C-XX REV X (REV MARKING PER PO)

CAGE CODE: 1HJX9 DATE OF MFGR: MM/YY

- WIRING FUNCTION: TABLE 1 WIRE RUN LIST
- 11. MANUFACTURE AND INSPECT IAW IPC/WHMA A-620 CLASS 2.

BILL OF MATERIALS											
ITEM NO.	PART NUMBER QTY		NAME	COMMENTS							
1	51245	AR	WIRE								
2	TE-32C-ASSY	1	CONNECTOR ASSEMBLY	INCLUDES HOUSING, FASTENERS, THUMBWHEEL. PROVIDED BY SUPPLYNET							
3	SN0072	1	РСВ								

				REF.	NUM	BER: SNO2	277		
UNLESS OTHERWISE SPECIFIED:		NAME	DATE	Siini	nlııNe	706 EXECUTIVE E	BLVD.		
DIMENSIONS ARE IN: INCHES	DRAWN	TC	10/09/15	anhi	nduc	VALLEY COTTAGE	E. NY 10989)	
TOLERANCES: .XX: ± 0.03 .XXX: ± 0.005	CHECKED	RJB	10/09/15	TITLE:				_	
ANGULAR: .X°: 1° .XX°: 0.5° BREAK EDGES: .005020 FILLETS: .005020 SUFACE FINISH:	COMMENTS:	MMENTS:			SIDE EXIT PRC-152 32 PIN DATA CABLE, J3 PORT				
OUT (GET II NOT).	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS			331 311					
GEOMETRIC TOLERANCING PER: ASME Y14.5 -2009	DRAWING IS THE SOLE PROPERTY OF SUPPLYNET, INC. ANY REPRODUCTION			SIZE	DWG.			REV	
MATERIAL: SEE DRAWING NOTES	IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SUPPLYNET INC.		B TE-32C-XX B						
FINISH: SEE DRAWING NOTES	IS PROHIBITED.								
DO NOT SCALE DRAWING CAGE CODE: 1HJX9					E: NA	WEIGHT:	SHEE	T 1 OF 1	