



- NOTES:
1. WIRING SHALL BE DONE IN ACCORDANCE WITH TABLE 1 WIRE RUN LIST.
  2. MARKING REQUIREMENTS:
    1. LABELS SHALL BE MARKED IN ACCORDANCE WITH MIL-STD-130 AS APPLICABLE.
    2. ADHESIVE LINED WRAP-AROUND LABEL MAY BE USED.
    3. LABELS SHALL BE WHITE WITH BLACK TEXT. REFER TO TABLE 2 FOR LABEL TEXT.
    4. LABELS SHALL BE PLACED WHERE SHOWN IN DRAWING.
  3. SOLDERING: IAW IPC-J-STD-001 CLASS 2 AS APPLICABLE
  4. ASSEMBLY TO BE 100% TESTED FOR SHORTS, CONTINUITY, AND JACKET RESISTANCE (100V @ 100MOHM MIN.)
  5. IDENTIFICATION: BAG AND IDENTIFY ON THE PACKAGING THE FOLLOWING INFORMATION FOR EACH PART DELIVERED.  
**PN:SN-M047-00430-001 REV. X (REV MARKING PER PO)**  
**CAGE CODE: 1HJX9**  
**MFD: MM/YY**
  6. MANUFACTURE AND INSPECT IAW IPC/WHMA A-620 CLASS 2.

TABLE 2: LABEL IDENTIFICATION		
ITEM NO.	LABEL TEXT	NOTES
A	SN-M047-00430-001 REV. X CAGE: 1HJX9 MFD: MM/YY	REV MARKING PER PO (SEE NOTE 2)

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	<div>SupplyNet</div> <div>706 EXECUTIVE BLVD SUITE B VALLEY COTTAGE, NY 10989</div>			
DIMENSIONS ARE IN: INCHES		DRAWN	MOB	04/27/22		TITLE:  <div>PRC-163 EUD USB CABLE, ODU TO USB-C</div>	
TOLERANCES: .XX: ± 0.03 .XXX: ± 0.005		CHECKED	RB	04/27/22			
ANGULAR: .X°: 1° .XX°: 0.5°		COMMENTS:					
BREAK EDGES: .005 - .020 FILLETS: .005 - .020 SUFACE FINISH:							
GEOMETRIC TOLERANCING PER: ASME Y14.5 -2009		<div>PROPRIETARY AND CONFIDENTIAL</div> <div>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SUPPLYNET, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SUPPLYNET INC. IS PROHIBITED.</div>					
MATERIAL: SEE DRAWING NOTES		SIZE		DWG. NO.		REV	
FINISH: SEE DRAWING NOTES		B		SN-M047-00430-001		C	
DO NOT SCALE DRAWING		CAGE CODE: 1HJX9		SCALE: NA		WEIGHT:	SHEET 1 OF 1