

SPECIFICATIONS						
IMMERSION	1 METER IN WATER / 30 MINUTES					
TEMPERATURE	-40°C (-40°F) TO +90°C (194°F)					
CONTINUITY TEST	CABLE ASSEMBLIES TO BE 100% TESTED FOR CONTINUITY OPEN & SHORTS					
RESISTANCE TEST	250V @100 MOhm , WIRE RESISTANCE 5.0 Ohm					
MANUFACTURE AND INSPECT	IAW IPC/WHMA A-620 CLASS 2					
SOLDERING	IAW IPC-J-STD-001 CLASS II AS APPLICABLE					

NOTES:

- 1. CABLE: 26 AWG, 19 CONDUCTOR, OD: 0.270 NOMINAL. POLYURETHANE INSULATION. OUTER SHIELD 38 AWG, TIN PLATED COPPER BRAID, 90% COVERAGE.
- 2. OVERMOLD MATERIAL: 90A POLYETHER-TYPE THERMOPLASTIC POLYURETHANE (TPU).
- 3. JACKET: BLACK MATTE FINISH.
- 4. IDENTIFICATION: BAG ANDINDENTIFY ON PACKAGING THE FOLLOWING INFORMATION FOR EACH PART DELIVERED. UOS PART MARKING ON THE WIRE IS PROHIBITED:

PN: TE-32MZ-A-XX REV X (REV MARKING PER PO)

CAGE CODE: 1HJX9 DATE OF MFGR: MM/YY

5. WIRING FUNCTION: TABLE 1 AND DRAWING SN0077.

BILL OF MATERIALS											
ITEM NO.	PART NUMBER	QTY	NAME COMMENTS								
1	51234	74"	CABLE	19C CABLE270 OD.							
				INCLUDES HOUSING, FASTENERS,							
2	TE-32M-ASSY	1	CONNECTOR ASSEMBLY	THUMBWHEEL. PROVIDED BY							
				SUPPLYNET							
3	SN0077	1	PCB	SUPPLYNET PROVIDED							

				PAR	T NUN	ΛBER:	SN00	079	
UNLESS OTHERWISE SPECIFIED:		NAME	DATE	Cuni	nlııNo		EXECUTIVE B	BLVD.	
DIMENSIONS ARE IN: INCHES	DRAWN	TC	08/19/16	Juh	hiduc	SUIT VAL	LEY COTTAGE	E. NY 10989	•
TOLERANCES: .XX: ± 0.03 .XXX: ± 0.005	CHECKED	RJB	08/19/16	TITLE:					_
ANGULAR: .X°:1° .XX°:0.5° BREAK EDGES: .005020 FILLETS: .005020 SUFACE FINISH:	COMMENTS:			REAR EXIT PRC-117G 32 PIN DATA CABLE ETHERNET/AUDIO/RS-232					Е
SUFACE FINISH.	PROPRIETARY THE INFORMATIO		-			IXI V L 17	/ (ODI	O / 10	202
GEOMETRIC TOLERANCING PER: ASME Y14.5 -2009	DRAWING IS THE SOLE PROPERTY OF SUPPLYNET, INC. ANY REPRODUCTION			SIZE	DWG.		. 7	\/\/	REV
MATERIAL: SEE DRAWING NOTES		WHOLE WITHOUT THE ION OF SUPPLYNET INC.		В	││ <mark></mark>	32N	۱Z-A	-X X	Α
FINISH: SEE DRAWING NOTES	IS PROHIBITED.								<i>,</i> ,
DO NOT SCALE DRAWING	CAGE CO	ODE: 1	HJX9	SCA	LE: NA	WEIGH	łT:	SHEET	1 OF 1

8 5 4 3 2